Llegrand

Radio wireless chimes





Pack	Cat.Nos	Radio chime kits
1	0 942 50	Essential kit Includes a chime and an IP 44 door bell with label holder Sound level: +/- 80 dB Number of ringtones: 32 Range approximately 50 m in free field Power supply: - chime: 2 x 1.5 V AA batteries (not included) - door bell: 1 CR2032 battery (included) White
1 1 1	0 942 53	Comfort kits Includes a round chime and a round IP 44 door bell with label holder Sound level: +/- 75 dB. Volume control Number of ringtones: 15 Range approximately 100 m in free field Unlimited number of additional chimes for 1 door bell Power supply: - chime: 3 x 1.5 V AA batteries (not included) except Cat. No. 0 942 54 (plug-in 230 V) - door bell: 1 CR2032 battery (included) White - battery-operated Anthracite - battery-operated White - plug-in 230 V
		Serenity kits Includes a square chime and a square IP 54 door bell with label holder Sound level: +/- 80 dB. Volume control Number of ringtones: 30 Ringtone customised via MP3 (software for creating MP3 melody provided in chime internal memory + USB cable included) Chime mute function Built-in flash Range approximately 200 m in free field Unlimited number of additional chimes for 1 door bell
1 1 1	0 942 70 0 942 71 0 942 72	

Pack	Cat.Nos	Accessories for Comfort and Serenity radio chime kits	
		White finish	
1	0 942 78	Comfort door bell - IP 44 Radio signal range 100 m Powered by 1 CR2032 battery (included)	
1	0 942 79	Serenity door bell - IP 54 Radio signal range 100 m Powered by 1 CR2032 battery (included)	
1	0 942 80	Motion detector - IP 20 Tiltable bracket for fixing on the wall or putting on a surface Radio signal range 150 m Detection range: 6-8 m Detection angle: 110° Powered by 3 x 1.5 V AAA batteries (not included)	

legrand





A reliable, easy-to-install wireless collection of radio chime kits,

designed for both residential and small commercial premises.



Exclusive and original LEGRAND design (round and square models)



Radio operating range differentiated according to range (50/100/200m)



Noise level: up to 80 dB



MP3 melody customization on SERENITY models (USB cable and software supplied)



Mutual compatibility of SERENITY and COMFORT range receivers and bell pushes



	ESSENTIAL Kit	0 942 50* 0 942 51*
06	COMFORT Kit	0 942 52
00	COMFORT Kit	0 942 53
Co	COMFORT Kit (Plug-in)	0 942 54
The state of the s	SERENITY Kit	0 94270
	SERENITY Kit	0 942 71
	Kit SERENITY Double	0 942 72
as thrown	COMFORT Bell push	0 942 78
No Durant	SERENITY Bell push	0 942 79
1000	IR sensor Fully compatible with Serenity and Comfort ranges	0 942 80

^{*} According to packaging

Llegrand

World Headquarters and International Department

87045 Limoges Cedex - France Tel.: + 33 (0) 5 55 06 87 87 Fax: + 33 (0) 5 55 06 74 55

WIRELESS CHIMES COLLECTION

Install it where you want with the sound you like









Bell push: IP 54

((•))) Radio operating range: 200 m





n 15 melodies

Bell push: IP 44

(((•))) Radio operating range: 100 m



- Fully compatible with Serenity and Comfort ranges
- Adjustable support
- IR detection: 8 m
- Radio operating range: 100 m





32 melodies

Bell push: IP 44

((•))) Radio operating range: 50 m



EX218019_Wireless_Chimes_Collection.indd 2 25/06/2018 09:45