



# 2325 G3 LED

## Planar LED downlight

- Multilumen and Multicolor
- Sustainable luminaires: 2325 S
- Flexible mounting

The 2325 LED G3 downlight is the perfect option for lighting refurbishments due to its versatility and flexibility. Multilumen technology provides three luminaire luminous fluxes and Multicolour offers a choice of light colours in one luminaire. With refurbishment rings it is suitable for most ceiling openings. The 2325 LED is ideal for reception areas, hotels, restaurants, sales areas, meeting and recreation rooms as well as corridors. Sustainable luminaires 2325 S with verified CO<sub>2</sub> compensation. With this you master the job!

### Why you'll get the job done with the 2325 G3 LED downlight

- NEW: Multilumen and Multicolour: Adjustable luminous flux (2,000 lm, 1,400 lm, 800 lm) and light colors (3,000 K, 4,000 K)
- NEW: With renovation rings suitable for ceiling openings from 150 mm to 250 mm
- Toolless ceiling installation due to quick mounting springs
- Very low recess depth (43 mm incl. control gear unit)
- Pleasant light effect due to uniform illumination
- High efficiency (up to 105 lm/W) and reliable service life (50,000 h, L65).
- Sustainable luminaires 2325 S with higher efficiency and service life.

### 2325 S - Sustainability at a glance

- Verified CO<sub>2</sub> compensation
- Higher energy efficiency: 120 lm/W
- Increased service life: 50,000 h, L70
- Modular design for optimum recycling

### 2325 LED at a glance

<b>Dimensions:</b>	Ø 170 x 43 mm; Ø 230 x 43 mm
<b>Luminaire luminous flux:</b>	2000 / 1400 / 800 (Multilumen)
<b>Colour temperature:</b>	3.000 K, 4.000 K
<b>Protection class:</b>	IP20 / IP44 (on room side) / IK02
<b>Safety class:</b>	II
<b>Weight:</b>	0,4 kg, 0,5 kg

### All versions of 2325 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
<b>CO<sub>2</sub> compensated / Multilumen</b>						
2325 G3 C05 S OA LED 20/14/08/ML-840 ET	7790940	2000 / 1400 / 800		4000	Ø 170 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL
2325 G3 C07 S OA LED 20/14/08/ML-840 ET	7791040	2000 / 1400 / 800		4000	Ø 230 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL
<b>Multi-colour / multi-lumen (light colour and luminous flux adjustable)</b>						
2325 G3 C05 OA LED 20/14/08/ML-8MC ET	7791140	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 170 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL
2325 G3 C07 OA LED 20/14/08/ML-8MC ET	7791240	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 230 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL

**Parts for 2325 LED**

Product reference	TOC	Description	Colour	Dimensions L x W x H [mm]	Weight
2325 G3 C05 SP 200	8120600	Mounting accessories / renovation ring for ceiling cutouts Ø 150 - 200 mm.	White	Ø 215 x 11	0,1 kg
2325 G3 C07 SP 250	8120500	Mounting accessories / renovation ring for ceiling cutouts Ø 200 - 250 mm.	White	Ø 275 x 11	0,1 kg